

Pursue Your Path



Get superior performance at exceptional value with the **Pathrider 130XL Pursuit**. Front and rear suspension combine with large 33 cm (13") wheels to handle rugged outdoor terrain. The easy-drive delta tiller allows for simple, one handed operation and LED lighting package enhances visibility for a safe and smooth ride.



Front Light Package



Rear Light Package



Suspension



**Performance & Comfort
at a Great Value**

SPECIFICATIONS

PATHRIDER® 130XL PURSUIT


SCT670571

Weight Capacity	159 kg (350 lbs.)
Front Tyre	33 cm (13")
Rear Tyres	33 cm (13")
Maximum Speed ¹	Up to 12.4 km/h (7.7 mph)
Ground Clearance ³	9.69 cm (3.81")
Turning Radius ³	170 cm (67")
Length/Width ³	135.9 cm (53.5") / 63.5 cm (25")
Seating ³	CRS Deluxe 18" w x 18" d (45.7 cm w x 45.7 cm d)
Seat-to-Ground	56.69 cm (22.31")
Weight (w/o Batteries)	73 kg (161 lbs.)
Seat-to-Deck	47 cm (18.5")
Battery Weight	18 kg (39 lbs.) each
Battery Requirements ^{4,5}	55 AH standard
Per Charge Range ^{1,2} (Max.)	Up to 25 km (15 miles)
Battery Charger	5 amp, off-board
Suspension	Front and rear
Weight of Heaviest Piece ^{3,6}	73 kg (161 lbs.) (frame is one piece)

FEATURES AND BENEFITS

- Superior performance at an affordable value
- Large 33 cm (13") pneumatic tyres for excellent outdoor performance
- Full lighting package including directional signals and angle-adjustable LED headlight
- Easy drive tiller with wraparound handles
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front and rear suspension handle rugged outdoor terrain
- Rear storage bag (standard)

COLOUR



Candy Apple Red

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical based calculations on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.